easiMARK DTF Hot/Warm Peel Film

product specification

This premium DTF transfer film is specifically crafted for direct-to-film transfer printing with aqueous inks. Suitable for nearly all textile surfaces, it ensures effective transfer without bleeding or unwanted powder. It is specially designed for hot peel application.

- Sheds excess powder perfectly
- Water based designed for recyclability
- Suitable for a huge range of textile application
- Coated with 5 layers of coating

- High ink load capacity with no bleed
- Stable throughout curing process
- Instant hot peel saving you time
- For use with aqueous pigmented inks only

composition	thickness (μ)	finish	
PET	75	matt both sides	

step by step guide

prepare	print	apply
keep the surface clean and free from dust before printing	print the material trim each transfer ready for application	temperature: 140 - 150°C for 10 - 15 seconds medium pressure hot/warm peel

Suitable for cotton, polyester and poly/cotton mixes.

recommendations

Use latex gloves when handling - fingerprints can affect the print quality. A test print and cut before each use is highly recommended due to variations in conditions of usage. Please wait 24 hours after pressing before washing

wash cold (mild detergent, inside out)

do not tumble drv

do not iron directly on the transfer

Do not use bleach or other aggressive chemical agents





Telephone: 01246 570570 e-mail: sales@victorydesign.co.uk website: www.victorydesign.co.uk