

### Technical Data Sheet

**GRAPHICS** - RI-MARK

Issue date : 09/03/2012 Date last modification : 09/03/2012

# 06327 - RI-MARK L101 GLOSS BLACK ULTRA REMOVABLE WK135

## Face Material

Self-adhesive material for plotter. Monomeric gloss finish vinyl. Liner that offers superior cuttability with conventional die-cutting and computer signmaking systems.

Type Colour and Finish Weight Thickness Monomeric vinyl Gloss black 95 g/m<sup>2</sup> ±10% ISO-536 70 µ ±10% ISO 534-80

#### Adhesive

Acrylic removable adhesive featuring good clarity and clean removability from glass, laminated plastics and crosslinked enamels. Not suitable for application on papers, PVC and air dried paints and varnishes.

Reference	AR801	
Туре	Acrylic removable	
Min. Appl. Temp.	+5°C	
Service Temp.	-40°C/+120°C	
Shear	High	
Tack	2 N/25mm FINAT FTM9	
Final Adhesion	2 N/25mm FINAT FTM2	

This adhesive complies with FDA 175.105.

#### Liner

Туре	One side siliconised clay coated Kraft	
Colour and Finish Weight	White 135 g/m² ±10%	PP-032 - ISO 536

#### Applications

Temporary traffic signage or other short-term applications where easy removability is required.

#### Printing Methods

Testing for suitability between media, printers and inks is always recommended prior to use. Testing for suitability between media, printers and inks is always recommended prior to use.

# Shelf life

12 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of  $~22^\circ\text{C}$   $\pm~2^\circ\text{C}$  and 50  $\pm~5\%$  of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A. Via Senatore Simonetta, 24 20867 Caponago (MB) ITALY e-mail:info@ritrama.com w w w . r i t r a m a . c o m

