

# Limo Film Premium 05

## product specification

Crafted with top-tier quality, this tint film effectively blocks 99% of harmful UV rays, safeguarding your skin and preserving your car's interior. With glare reduction of up to 94%, it ensures a more comfortable driving experience. Its deep limo tint not only adds a touch of elegance to your car but also shields it from unwanted attention.

### specification

Data calculated based on film applied to clear glass 3 mm thick  
(\*on double glazing 4-16-4)

|                                      |          |
|--------------------------------------|----------|
| Ultraviolet transmission             | 1%       |
| Visible light transmission           | 6%       |
| Reflection of external visible light | 5%       |
| Reflection of internal visible light | 5%       |
| Total solar energy rejected          | 32%      |
| Total solar energy rejected 2        | 32%      |
| Solar ratio:                         |          |
| Solar energy reflection              | 55%      |
| Solar energy absorption              | 33%      |
| Solar energy transmission            | 12%      |
| Reduction in Solar Glare             | 94%      |
| g-value                              | 0.6      |
| u-value                              |          |
| Shading coefficient                  |          |
| Installation type                    | Internal |
| Roll length                          | 30.5m    |
| PET / PVC construction               | PET      |
| Thickness                            | 25µ      |

Colour: BLACK

### maintenance instructions

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

*Non-contractual data, Victory Design Ltd reserves the right to modify the composition of its films at any time.*

### installation advice

Vertical installation and on standard glass surface\*

|                                |         |
|--------------------------------|---------|
| Clear single pane              | Yes     |
| Tinted single pane             | Caution |
| Reflective tinted single pane  | No      |
| Clear double pane              | No      |
| Tinted double pane             | No      |
| Reflective tinted double pane  | Yes     |
| Gas-filled double pane - Low E | No      |
| STADIP EXT. clear double pane  | No      |
| STADIP INT. clear double pane  | No      |

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>, contact us for definitive details or to obtain a thermal chock analysis report.

lifetime warranty

3 years storage  
(-5 - +40°C)

REACH  
RoHS  
compliant

### construction

1. "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
2. Dyed polyester without optical distortion
3. PS adhesive, glass polymerization within 15 days
4. Protection release liner, disposable after installation

